

Shaped electric-welded tubes

TU U 14-8-41-2001

Used for constructions of conventional purpose.

Pipe dimensions and weight

Outer dimensions, mm		Weight per meter, kg, for wall thickness, mm											
A	B	1,0	1,2	1,4	1,5	1,6	1,8	2,0	2,2	2,5	2,8	3,0	3,2
17	17	0,485	0,576	0,659	0,700	0,739	0,815	0,888	0,957	1,05	-	-	-
17	25	0,614	0,727	0,831	0,888	0,928	1,04	1,14	1,23	1,37	-	-	-
20	20	0,583	0,689	0,791	0,841	0,890	0,985	1,08	1,16	1,29	-	-	-
21	21	0,614	0,727	0,835	0,888	0,940	1,04	1,14	1,23	1,37	1,49	1,57	-
25	15	0,583	0,689	0,767	0,841	0,914	0,985	1,08	1,16	1,29	-	-	-
25	25	0,740	0,877	1,01	1,07	1,14	1,27	1,39	1,51	1,68	1,86	1,95	-
26	26	-	0,915	1,05	1,12	1,19	1,32	1,45	1,58	1,76	1,93	2,05	2,15
28	25	-	0,934	1,08	1,15	1,22	1,35	1,49	1,61	1,80	1,98	2,09	2,20
30	30	-	1,07	1,23	1,31	1,39	1,55	1,70	1,86	2,07	2,29	2,42	2,55
40	20	-	1,07	1,23	1,31	1,39	1,55	1,70	1,86	2,07	2,29	2,42	2,55
40	25	-	-	1,34	1,43	1,52	1,69	1,86	2,03	2,27	2,51	2,66	2,81
40	28	-	-	1,41	1,50	1,59	1,78	1,95	2,13	2,39	2,64	2,80	2,96
40	30	-	-	1,45	1,55	1,64	1,83	2,02	2,20	2,47	2,73	2,89	3,05
40	40	-	-	1,67	1,78	1,89	2,12	2,33	2,55	2,86	3,16	3,36	3,56
50	25	-	-	1,56	1,66	1,77	1,97	2,17	2,37	2,66	2,95	3,13	3,31
50	30	-	-	1,67	1,78	1,89	2,12	2,33	2,55	2,86	3,16	3,36	3,56
60	30	-	-	1,89	2,02	2,15	2,40	2,65	2,89	3,25	3,60	3,83	4,06
60	35	-	-	2,00	2,14	2,27	2,54	2,80	3,06	3,45	3,82	4,07	4,31

Lengths supplied:

- off-gage length of 1.5 to 11.0 m;
- specific cut length of 5.0 to 9.0 m;
- multiple specific cut length with any multiplicity not exceeding low limit set for cut-to length tubes.

Steel hardness:

Steel grade	Chemical compound according to
St1sp, St1kp, St1ps, St2sp, St2kp, St2ps, St3sp, St3kp, St3ps	GOST 380
08, 08kp, 08ps, 10, 10kp, 10ps, 15, 15kp, 15ps, 20, 20kp, 20ps	GOST 1050
08H0	GOST 9045